# Electrolux Cold Rooms

# -10/-21° - 10/11,7 m³ - Split unit

Electrolux cold rooms are available in a vast range of different sizes and functionalities. They are designed to work in tropical temperatures (+43°C). The range consists of coolers (-2/+8°C) with panels 60 mm in thickness, freezer cold rooms (-10/-21°C) with panels 100 mm in thickness and with built-in or remote refrigerating unit. The three models detailed on this sheet are split unit freezers cold rooms with usable volume of 10 to 11,7 cubic meters. Models come with panels, gas pre-charged cooling unit and piping.




Shelving as accessory


CONSTRUCTION

- Very short assembly time. Expert refrigeration knowledge is not required for installation.
- New vacuum injection technology which permits to have significant enhancement on the performances of the panels and high quality.
- Panels are cladded inside and outside with anti-scratch prepainted galvinized steel. Polyurethane foam insulation. CFC and HCFC free.
- Rounded internal and external corners. All edges are radiused.
- Anti-slip walk-in floor.
- The fast-fit centering system allows perfect alignment of the panels. These new fasteners are made of high resistant composite materials and guarantee perfect grip of all components.
- Airtight panels connection. All sides of panels have PVC gasket foamed in place to assure airtight and secure fitting. Any other sealing between panels on site is eliminated.
- The refrigeration unit is mounted on a modular panel for easy installation and quick set-up of the cold room. All the refrigeration units are tropicalized (+43°C) and use R404A refrigerant and are supplied with a high/low temperature alarm.
- If the floor on which the cold rooms will be installed presents irregularities or unevenness up to 1 cm, then the surface of the floor should be levelled.


PERFORMANCES

- Defrosting through heated gas with re-evaporation of defrosting water permits to reduce the total power installed, shorten defrosting time and limit the warming of the cold room.
- All models are equipped with internal lighting (waterproof IP54) mounted on the refrigerating unit panel.
- The control panel includes: luminous ON/OFF switch, internal lighting switch, cold room functioning indicator, defrost cycle indicator, temperature and thermostat control with digital display.
- The right-hinged door is available as standard (left-hinged door on request) and constructed with smooth rounded profiles, cam-lift action hinges, airtight magnetic gasket and high insulation thus allowing to reduce energy and operating costs.
- Newly designed handle complete with lock and interior safety release to prevent entrapment when the door is accidentally locked from outside.
- HACCP monitoring is possible trough a serial port supplied on all models.
- Conform to ruling European safety and hygiene standards and H marked.


102337




102352




102334




2009-10-06

| | CR24F100R<br>102337 | CR28F117R<br>102352 | CR20F117R<br>102334 |
|---|---|---|---|
| **LEGEND** | | | |
| EI - Electrical connection | 380/400 V, 3N, 50 | 380/400 V, 3N, 50 | 380/400 V, 3N, 50 |
| RI - Remote refrigeration connection | ● | ● | ● |
| **TECHNICAL DATA** | | | |
| External dimensions - mm | | | |
| width | 2630 | 3030 | 2230 |
| depth | 2230 | 2230 | 3030 |
| height | 2230 | 2230 | 2230 |
| Compressor power - HP | 2.2 | 2.2 | 2.2 |
| Electrical power - kW | 1.6 | 1.6 | 1.6 |
| Net weight - kg. | 514 | 563 | 563 |
| Power supply - V, phases, Hz | 380/400 V, 3N, 50 | 380/400 V, 3N, 50 | 380/400 V, 3N, 50 |
| Usable surface area - m² | 4,93 | 5,74 | 5,74 |
| Usable volume - m³. | 10,0 | 11,7 | 11,7 |
| **ACCESSORIES** | | | |
| ALUM.SHELV.,POLY.TIERS-COLDROOM 203X283 | | | 137099 |
| ALUM.SHELV.,POLY.TIERS-COLDROOM 243X203 | 137102 | | |
| ALUM.SHELV.,POLY.TIERS-COLDROOM 283X203 | | 137106 | |
| DOOR MICROSWITCH | 102441 | 102441 | 102441 |
| GRAPHIC TEMPERATURE RECORDER | 102025 | 102025 | 102025 |
| KIT HACCP ADV.CONNECTION FOR COLD ROOMS | 102021 | 102021 | 102021 |
| PLASTIC CURTAIN FOR 65CM DOOR CLEARANCE | 102027 | 102027 | 102027 |
| PRINTER FOR HACCP BASIC VERSION REFRIG. | 881457 | 881457 | 881457 |
| PRINTER FOR TEMPERATURE RECORDER | 102026 | 102026 | 102026 |